SOLARIS®

FLARE JR.



Little brother of the fabulous Solaris Flare, Winner Live Design Product of the Year and PLASA Sustainability Award

Super Bright LED RGBW Wash/Strobe/Blinder

MORE SAVINGS! Simultaneous color wash and strobe in ONE fixture – Saves labor, time, space, energy, and cost.

MORE SMOOTH! Instantaneous RGBW color mixing with 1200Hz refresh rate – Smooth on-camera dimming.

MORE VERSATILE! Pixel-map feature divides into 1, 2, or 4 sections for ultimate control.

MORE SATURATED COLORS! Intense, deep reds and blues. Ultra-bright greens. Brilliant camera-friendly whites.

MORE FLEXIBLE! 36-degree beam angle optimized for most applications. 22, 54, & 70-degree available by special order.

C SA US CE RDM Powered By CREE LEDs Available with Wireless Option

KASMER Filter Holder!



Worldwide Exclusive Distribution

sales@tmb.com

Los Angeles +1 818.899.8818

London +44 (0)20.8574.9700

tmb www.tmb.com

New York +1 201.896.8600

Beijing +86 10.8492.1587

Toronto +1 519.538.0888

© 2021, TMB. All rights reserved. LITSOLFLAREJR Effective: 28 June 2021
Specifications are subject to change without notice. This information supersedes all previously supplied information.


SOLARIS®


FLARE JR.


Specifications	
Light sources	32 10W CREE© LEDs (divided in to 4 pixels)
Beam spread	36°
Colors	4- R, G, B, W
Average color wavelength (manufacturer rated)	Red: 625 nm
	Green: 530 nm
	Blue: 460 nm
	White: >5700K
Refresh rate	1200 Hz
Intensity control	16-bit or 8-bit
Control	DMX-512
Wireless control	Wireless option available by special order
AC power	90-277 VAC universal input, 50/60 Hz
Cooling	Air-cooled fan
Operating temperature	-20°C - +40°C
DMX channels	3-24 depending on control mode
DMX connectors	In/Out - XLR 5-pin F/M
Max. power draw	~400 W
Power connectors	In- PowerCon 20A blue + THRU- PowerCon grey
Fixing	Adjustable yoke
Fixture body	Powdercoated steel
Unit dimensions (HxWxD)	6.1 x 13.4 x 5.3 in [15.5 x 34 x 13.5 cm]
Shipping dimensions (HxWxD)	14 x 14 x 10 in [35.6 x 35.6 x 25.4 cm]
Unit weight	10.6 lb [4.8 kg]
Shipping weight	13 lb [5.9 kg]

Specifications and features are subject to change without notice.

Ordering Codes	
Ordering Code	Item
SOLFJ36R	Flare Jr fixture
SOLFJ36RW	Flare Jr fixture, wireless
SOLFJ36RWADD	Flare Jr wireless adder
SOLFJRKAS	Flare Jr Kasmer diffusion/filter holder
SOLFJRBKAS	Flare Jr Kasmer barndoor







sales@tmb.com
Los Angeles +1 818.899.8818
London +44 (0)20.8574.9700
tmb www.tmb.com
New York +1 201.896.8600
Beijing +86 10.8492.1587
Toronto +1 519.538.0888

© 2021, TMB. All rights reserved. LITSOLFLAREJR Effective: 28 June 2021
Specifications are subject to change without notice. This information supersedes all previously supplied information.